Verified RealEstate™

RE REGULATORY RECORD

RERA Document

The document as the regulator published it, reproduced in full behind this page.

Published for reference. The authority's own register is the operative record.

Verified RealEstate™
3/350/2 Mettukuppam,
OMR Thoraipakkam,
Chennai 600 097, India

hello@verified.realestate
+91 9996 12 9996
verified.realestate

DIGITALLY VERIFIED RECORD

Dr. ALEX JACOB
B.E.,M.Tech (Str).,Ph.D (Hon).,Dip. Bdg.Sc (Aust)., M.I.E (Aust), M.I.E (Ind)
CONSULTING ENGINEER
Old No.41/A, New No.70, Beach Road,Kalakshetra Colony,
Besant Nagar, Chennai - 600 090.

044 - 24910945
+91-98401 59550
alexjacobuc@gmail.com
www.unitedconsultants.in

18.09.2025

STABILITY CERTIFICATE

The detailed engineering and structure design of the Commercial Building **"SUMMIT-1"** comprising of Basement, Ground +10 floors to be constructed at T.S. Nos.1 Block No.5 Ward No 30, Ward AD at Uppilipalayam Village and T.S.Nos:18&22, Block No.9 Ward AC, at Sowripalayam Village, Trichy Main Road, Coimbatore South Taluk, Coimbatore District, has been done by us based on the report of geotechnical Investigation (soil test) done by Geo design India Pvt. Ltd., Report No. Ref: GEO-G-239-2023-24 Dated: 13.02.2024- 17.02.2024 and considering the functional requirement of the building;

2. It is certified that among other factors, the proposed building has been designed to resist earthquake. I have checked various parameters and found that the proposed building would be safe.

3. I further certify that:

i. The minimum grade of concrete is **M25**

ii. The design and analysis have been done using the code of practice for plain and reinforced concrete as per IS 456, design loads as per IS Codes No **IS-875 and IS - 1893** and design of earthquake resistant structure as per IS Code No **IS:1893**

4. The building will be **safe and sound** when used for the purpose for which it is designed.

For SREE SHARADHA AMBAL FOUNDATIONS

Partner

For SREE SHARADHA AMBAL FOUNDATIONS

Partner

(Dr.ALEX JACOB)

Dr. ALEX JACOB
B.E., M.Tech(Str), Ph.D(Hon),
M.I.E. (Aust), M.I.E. (Ind)
STRUCTURAL ENINEER
70, BEACH ROAD, KALAKSHETRA COLONY,
Chennai - 600 090.
REG No. SE/GR-I/24/02/001
REG No. RSE100392025

Client: M/s. Sree Shardha Ambal Foundation (POA), Premier Hi-Tech Industries & Two Others (Owners)

Project: THE PROPOSED CONSTRUCTION OF HIGH RISE COMMERCIAL BUILDING CONSISTING OF BASEMENT FLOOR + GROUND FLOOR + 10 FLOORS AT T.S.No; 1, BLOCK No: 5, WARD No: AD-UPPILIPALAYAM VILLAGE, T.S.No: 22 & 18, BLOCK No: 9, WARD No: AC-SOWRIPALAYAM VILLAGE, TRIVHY MAIN ROAD, COIMBATORE CORPORATION, COIMBATORE DISTRICT

Structural Consultant: M/s. UNITED CONSULTANTS
41/A, Beach road, Sea point apartments
Kalashetra colony, Besant nagar, Chennai-90

Title: COMMERCIAL BUILDING

For SREE SHARADHA AMBAL FOUNDATIONS

Partner


For SREE SHARADHA AMBAL FOUNDATIONS

Partner

Dr. ALEX JACOB
B.E., M.Tech(Str), Ph.D(Hon),
M.I.E. (Aust), M.I.E. (Ind)
STRUCTURAL ENINEER
70, BEACH ROAD, KALAKSHETRA COLONY,
Chennai - 600 090.
REG No. SE/GR-I/24/02/001
REG No. RSE100392025

BUILDING DESCRIPTION

- The Proposed Construction of commercial building Extended Single Basement + Ground Floor + 10 Floors.
- Height of Building above ground level is 34.93m. (From Ground floor to Terrace floor)
- Basement floor used for Parking and the remaining upper floors used for Commercial purpose.
- The structure comprises of RC Shear wall, column, Beam & Slab.
- Raft foundation provided as per soil test report.



For SREE SHARADHA AMBAL FOUNDATIONS

Partner

3D VIEW

Dr. ALEX JACOB
B.E., M.Tech(Str), Ph.D(Hon),
M.I.E. (Aust), M.I.E. (Ind)
STRUCTURAL ENINEER
70, BEACH ROAD, KALAKSHETRA COLONY,
Chennai - 600 090.
REG No. SE/GR-I/24/02/001
REG No. RSE100392025

For SREE SHARADHA AMBAL FOUNDATIONS

Partner

GRADE OF CONCRETE & STEEL

• Raft foundation	:	M35
• Columns	:	M40
• RC Wall	:	M25
• Beams	:	M25
• Slabs	:	M25
• Staircase	:	M25

• Reinforcement of Grade Fe-500 is used for RCC design

LOADS

- Following Codes are used for designing members.
- IS 875 : 1987 (Part 1) Dead loads
- IS 875 : 1987 (Part 2) Live loads
- IS 875 : 2015 (Part 3) Wind loads
- IS 1893 : 2016 (Part 1) Earthquake loads
- IS 13920 : 2016 Ductile Design and Detailing of Reinforced concrete Structures

For SREE SHARADHA AMBAL FOUNDATIONS

Partner

For SREE SHARADHA AMBAL FOUNDATIONS

Partner

Dr. ALEX JACOB
B.E., M.Tech(Str), Ph.D(Hon),
M.I.E. (Aust), M.I.E. (Ind)
STRUCTURAL ENINEER
70, BEACH ROAD, KALAKSHETRA COLONY,
Chennai - 600 090.
REG No. SE/GR-I/24/02/001
REG No. RSE100392025

SUPER STRUCTURE DATA

Number of floors - Single Basement + Ground + 10 upper floors Height of each

Floors - 3.11 m

Total height of Building - 34.93 m, excluding Headroom & LMR

WALL PROPERTIES

- Lift RC wall thickness - 0.2m
- Modelling Type - Shell Thin

SLAB PROPERTIES

- Basement floors RC slab thickness - 0.45/0.2/0.15/0.12m
- Typical Floor RC slab thickness - 0.45/0.2/0.15/0.12m
- Modelling Type - Shell Thin

DEAD & LIVE LOADS

DEAD LOADS

- This comprises of self-weight of various structural elements indicated below:
- Self-weight of RC wall, column, Beam, slab and staircase.
- Floor and Roof finishes.
- Self-weight of the modelled elements is calculated by ETABS through SELF WEIGHT command.

LIVE LOADS

These loads are considered for the analysis in addition to dead loads as follows,

- Bath/Shower & Toilet = 2.0 kN/m^2
- commercial floor area = 5.0 kN/m^2
- Activity room = 5.0 kN/m^2
- Cafeteria = 5.0 kN/m^2
- Lobby, Balcony, Staircase = 4.0 kN/m^2
- AHU & Electrical Rooms = 5.0kN/m^2 or as per actuals

For SREE SHARADHA AMBAL FOUNDATIONS

Partner

For SREE SHARADHA AMBAL FOUNDATIONS


Partner

Dr. ALEX JACOB
B.E., M.Tech(Str), Ph.D(Hon),
M.I.E. (Aust), M.I.E. (Ind)
STRUCTURAL ENINEER
70, BEACH ROAD, KALAKSHETRA COLONY,
Chennai - 600 090.
REG No. SE/GR-I/24/02/001
REG No. RSE100392025

- Ramp, Parking = 5.0 kN/m^2
- Lift Machine rooms = 10.0 kN/m^2 or as per actuals
- Live Load on Roof =2 kN/m^2

SEISMIC INPUT

- Height of the Building, H = 34.9 m
- Seismic Zone = III
- Seismic Zone Factor, Z = 0.16
- Importance Factor, I = 1.2
- Response Reduction Factor, R = 3
- Percentage Damping = 5%
- Soil Type = III
- Avg. response acc. coefft. Sa/g = As per IS: 1893: 2016



For SREE SHARADHA AMBAL FOUNDATIONS

Partner

For SREE SHARADHA AMBAL FOUNDATIONS


Partner

Dr. ALEX JACOB
B.E., M.Tech(Str), Ph.D(Hon),
M.I.E. (Aust), M.I.E. (Ind)
STRUCTURAL ENINEER
70, BEACH ROAD, KALAKSHETRA COLONY,
Chennai - 600 090.
REG No. SE/GR-I/24/02/001
REG No. RSE100392025

WIND LOAD INPUT

The building located in Coimbatore region and the wind parameters are considered as per IS 875 part: 3

- Wind Speed = 39 m/s
- Terrain Category = 2
- Importance factor = 1
- Risk Coefficient, K1 = 1
- Topography, K3 = 1
- Importance factor for Cyclonic Region, k4 = 1



For SREE SHARADHA AMBAL FOUNDATIONS


Partner

For SREE SHARADHA AMBAL FOUNDATIONS

Partner


Dr. ALEX JACOB
B.E., M.Tech(Str), Ph.D(Hon),
M.I.E. (Aust), M.I.E. (Ind)
STRUCTURAL ENINEER
70, BEACH ROAD, KALAKSHETRA COLONY,
Chennai - 600 090.
REG No. SE/GR-I/24/02/001
REG No. RSE100392025

MASS SOURCE



DYNAMIC ANALYSIS

- Height of the Building, H = 34.9 m
- Seismic Zone = III
- Seismic Zone Factor, Z = 0.16
- Importance Factor, I = 1.2
- Response Reduction Factor, R = 3
- Percentage Damping = 5%
- Soil Type = III



For SREE SHARADHA AMBAL FOUNDATIONS

Partner

For SREE SHARADHA AMBAL FOUNDATIONS

Partner

Dr. ALEX JACOB
B.E., M.Tech(Str), Ph.D(Hon),
M.I.E. (Aust), M.I.E. (Ind)
STRUCTURAL ENINEER
70, BEACH ROAD, KALAKSHETRA COLONY,
Chennai - 600 090.
REG No. SE/GR-I/24/02/001
REG No. RSE100392025

LOAD COMBINATIONS

Load combinations as per IS 1893:2016

1.5(DL+LL)
1.2(DL+LL+EQX)
1.2(DL+LL-EQX)
1.2(DL+LL+EQY)
1.2(DL+LL-EQY)
1.2(DL+LL+WLX)
1.2(DL+LL-WLX)
1.2(DL+LL+WLY)
1.2(DL+LL-WLY)
1.2(DL+LL+RSX)
1.2(DL+LL-RSX)
1.2(DL+LL+RSY)
1.2(DL+LL-RSY)
0.9DL+1.5EQX
0.9DL-1.5EQX
0.9DL+1.5EQY
0.9DL-1.5EQY
0.9DL+1.5WLX
0.9DL-1.5WLX
0.9DL+1.5WLY
0.9DL-1.5WLY
0.9DL+1.5RSX
0.9DL-1.5RSX
0.9DL+1.5RSY
0.9DL-1.5RSY
1.5(DL+EQX)
1.5(DL-EQX)
1.5(DL+EQY)
1.5(DL-EQY)
1.5(DL+WLX)
1.5(DL-WLX)
1.5(DL+WLY)
1.5(DL-WLY)
1.5(DL+RSX)
1.5(DL-RSX)
1.5(DL+RSY)
1.5(DL-RSY)

MAXIMUM DISPLACEMENT

ALLOWABLE MAXIMUM DISPLACEMENT = 139.6 mm for wind & 69.8mm for seismic

- EQ-X = 34 mm
- EQ-Y = 29.5 mm
- RS-X = 40.7 mm
- RS-Y = 34.4 mm

For SREE SHARADHA AMBAL FOUNDATIONS

Partner

For SREE SHARADHA AMBAL FOUNDATIONS

Partner

Dr. ALEX JACOB
B.E., M.Tech(Str), Ph.D(Hon),
M.I.E. (Aust), M.I.E. (Ind)
STRUCTURAL ENINEER
70, BEACH ROAD, KALAKSHETRA COLONY,
Chennai - 600 090.
REG No. SE/GR-I/24/02/001
REG No. RSE100392025

MAXIMUM STOREY DRIFT

ALLOWABLE STOREY DRIFT = 0.004*H

- EQ-X = 0.0012
- EQ-Y = 0.0011
- RS-X = 0.0014
- RS-Y = 0.0010

STOREY SHEAR

- EQ-X = 4824 kN
- EQ-Y = 4801 Kn
- RS-X = 6275 kN
- RS-Y = 5999 kN

MODEL MASS PARTICIPATING RATIOS

Modal Participating Mass Ratios

File Edit Format-Filter-Sort Select Options

nits: As Noted Hidden Columns: No Sort: None

ilter: None

Modal Participating Mass Ratios

Case	Mode	Period sec	UX	UY	UZ	SumUX	SumUY	SumUZ	RX	RY	RZ	SumRX	SumRY	SumRZ
Modal	1	1.688	0.5154	0.1983	0	0.5154	0.1983	0	0.0753	0.184	0.0264	0.0753	0.184	0.0264
Modal	2	1.513	0.0307	0.2505	0	0.5462	0.4488	0	0.1029	0.0091	0.4476	0.1781	0.193	0.4741
Modal	3	1.026	0.1847	0.2657	0	0.7309	0.7145	0	0.1152	0.0833	0.2538	0.2933	0.2764	0.7279
Modal	4	0.481	0.091	0.0218	0	0.8219	0.7364	0	0.0665	0.2971	0.0102	0.3598	0.5734	0.7381
Modal	5	0.416	0.0002	0.062	0	0.8221	0.7984	0	0.1603	0.0013	0.0733	0.5201	0.5748	0.8115
Modal	6	0.269	0.044	0.0657	0	0.8661	0.8641	0	0.144	0.0956	0.0586	0.6642	0.6704	0.8701
Modal	7	0.234	0.0401	0.0068	0	0.9062	0.8709	0	0.013	0.075	0.006	0.6771	0.7454	0.8761
Modal	8	0.201	3.025E-05	0.0262	0	0.9063	0.8971	0	0.0505	4.693E-05	0.0282	0.7277	0.7454	0.9043
Modal	9	0.176	1.427E-05	8.497E-07	0	0.9063	0.8971	0	2.761E-06	1.465E-05	0.0001	0.7277	0.7455	0.9044
Modal	10	0.157	0.0003	0.0001	0	0.9066	0.8971	0	0.0001	0.0007	0.0014	0.7278	0.7461	0.9057
Modal	11	0.141	0.0196	0.0051	0	0.9261	-0.9022	0	0.0134	0.0561	0.0045	0.7412	0.8022	0.9102
Modal	12	0.135	0.0153	0.0195	0	0.9414	0.9217	0	0.0401	0.0331	0.0138	0.7812	0.8353	0.924

For SREE SHARADHA AMBAL FOUNDATIONS

Partner

For SREE SHARADHA AMBAL FOUNDATIONS

Partner

Dr. ALEX JACOB
B.E., M.Tech(Str), Ph.D(Hon),
M.I.E. (Aust), M.I.E. (Ind)
STRUCTURAL ENINEER
70, BEACH ROAD, KALAKSHETRA COLONY,
Chennai - 600 090.
REG No. SE/GR-I/24/02/001
REG No. RSE100392025

Design of column with Biaxial Moment SHORT COLUMN

The values are Displayed in Blue color are the Input valu

Column No = C1, STAAD - 17

Design Forces From STAAD Load Case = 100

1. Axial Load on column	=	25300 KN			
2. Bending moment along x-x, Mux	=	861 KN.m	Load Case	=	1
3. Bending moment along y-y, Muy	=	600 KN.m	Load Case	=	1

Design Datas


1. Compressive strength of Concrete, Fck	=	40 N/mm^2
2. Yield Strength of steel, Fy	=	500 N/mm^2
3.Diameter of Longitudinal Reinforcement,	=	32 mm
4.Diameter of lateral Reinforcement,	=	8 mm
5. Clear cover to the reinforcement, C	=	40 mm
6. Type of column	=	Rectangular
7. Size of Column	=	b x d
	=	900 x 900 mm
8. Unsupported Length of Column along x-x,L_x	=	3.2 m
9. Unsupported Length of Column along y-y,Ly	=	3.2 m
10. Effective length factor,	=	0.65
11. Effective Length of Column, along x-x, L_x	=	2.08 m
12. Effective Length of Column, along y-y, Ly	=	2.08 m


Check for leff/D


Effective length,lex/Lateral dimensions = L_{ex} / D
= 2.31
= 2.31< 12
= Short Column


Effective length,ley/Lateral dimensions = L_{ex} / b
= 2.31
= 2.31< 12
= Short Column

Section Geometry









4 Check for Minimum Eccentricity

Applied eccentricties

ex = Mux/Pu
= 861/25300
= 34.032 mm

ey = Muy/Pu
= 600/25300
= 23.715 mm

Minimum eccenticity

e_{xx} = (lex/500)+(D/30)
= (2080/500) + (900/30)
= 34.16 mm or 20 mm
= 34.16 mm

e_{yy} = (ley/500)+(D/30)
= (2080/500) + (900/30)
= 34.16 mm or 20 mm
= 34.16 mm

5 Moment due to Eccentricity

m_{uex} = Pu x e_{xx}
= (25300x34.16)/1000
= 864.25 KN.m

m_{uey} = Pu x e_{yy}
= (25300x34.16)/1000
= 864.25 KN.m

6 Design Moment

mux = Mux or muex
= 864.25 KN.m

muy = Mux or muey
= 864.25 KN.m

For SREE SHARADHA AMBAL FOUNDATIONS

Partner

For SREE SHARADHA AMBAL FOUNDATIONS

Partner

Dr. ALEX JACOB
B.E., M.Tech(Str), Ph.D(Hon),
M.I.E. (Aust), M.I.E. (Ind)
STRUCTURAL ENINEER
70, BEACH ROAD, KALAKSHETRA COLONY,
Chennai - 600 090.
REG No. SE/GR-I/24/02/001
REG No. RSE100392025

7 Calculation of Longitudinal reinforcement

Assume percentage of reinforcement = 4.7 %

Asc, required = 4.7/100x 900x900

= 38070 mm^2

No of bars = 48 Nos

Asc,,Provided = 38584 mm^2

pt, provided = 4.763 %

Moment Capacity Along x Direction

(Pu/fck b D) = (25300000/40 x 900 x 900)

= 0.78

p/fck = 4.763/40

= 0.12

d'/D = 40/900

= 0.04

From interaction chart, SP16 [chart 48]

$Mux1/fck\ b\ D^2$ = 0.1

Mux1 = 0.1 x 900x900x900x40

= 2916 KN.m

Moment Capacity Along y Direction

(Pu/fck b D) = (25300000/40 x 900 x 900)

= 0.78

p/fck = 4.763/40

= 0.1191

b'/D = 40/900

= 0.04

From interaction chart, SP16 [chart 50]

$Muy1/fck\ b\ D^2$ = 0.09

Muy1 = 0.09 x 900x900x900x40

= 2624.4 KN.m

8 Check for Moment Capcity

$(Mux/Mux1)^{an} + (Muy/Muy1)^{an} < 1$

Puz = (0.45 fck.Ac) +(0.75 fy -0.45fck)Asc

For SREE SHARADHA AMBAL FOUNDATIONS

Partner

For SREE SHARADHA AMBAL FOUNDATIONS

Partner

Dr. ALEX JACOB
B.E., M.Tech(Str), Ph.D(Hon),
M.I.E. (Aust), M.I.E. (Ind)
STRUCTURAL ENINEER
70, BEACH ROAD, KALAKSHETRA COLONY,
Chennai - 600 090.
REG No. SE/GR-I/24/02/001
REG No. RSE100392025

Ac	=	810000 mm^2	
Puz	=	28354.488 KN	For an v
Pu/Puz	=	0.892	
an	=	2	

$(Mux/Mux1)^{an} + (Muy/Muy1)^{an}$ = 0.196

0.196 < 1


O.K

9 Calculation of Lateral Reinforcement

Spacing of ties

1. Least Lateral Dimensions of column	=	900 mm
2. Sixteen times the least dia of Longi bar	=	512 mm
3. 300mm	=	300 mm
Adopt Spacing	=	300 mm

10 Details



Y8@300mm c/c

No of bars = 32mm 48 Nos

Dr. ALEX JACOB
B.E., M.Tech(Str), Ph.D(Hon),
M.I.E. (Aust), M.I.E. (Ind)
STRUCTURAL ENINEER
70, BEACH ROAD, KALAKSHETRA COLONY,
Chennai - 600 090.
REG No. SE/GR-I/24/02/001
REG No. RSE100392025


For SREE SHARADHA AMBAL FOUNDATIONS

Partner

For SREE SHARADHA AMBAL FOUNDATIONS

Partner

SLAB DETAILS

	Design of Two way Slab	The values are Displayed in Blue color are the Input values	References
1	Design Datas		
			
	1. Eff. Shorter span between c/c support, Lx	= 6.9 m	(Eff. Span,As per IS456:2000, clause 22.2 (b))
	2. Eff.Longer span between c/c support, Ly	= 7.1 m	
	3. Compressive strength of Concrete, Fck	= 25 N/mm^2	
	4. Yield Strength of steel, Fy	= 500 N/mm^2	
	5.Diameter of Reinforcement, (Shoter span)	= 12 mm	
	6.Diameter of Reinforcement, (Longer span)	= 12 mm	
	7. Fire resistance in hours	= 1.5 hrs	(Nominal cover, As per IS456:2000, Table 16A, clauses 21.4 and 26.4.3 and Fig 1
	8. Nominal cover to the reinforcement, C	= 20 mm	
2	Assume trial depth of slab		
	Span/depth, ratio l/d (Basic value)	= 26	(Span/depth ratio,As per IS:456:2000, Clause 23.2.1)
	Assume modification factor, M.F	= 1.5	
	depth of slab	= (Span/B.V x M.F)	
		= (6.9 x 1000) / (26 x 1.5)	
		= 176.92 mm	
	Overall depth required, D	= (d+cc+1/2 dia of bars)	
		= 176.92 + 20+ 12 /2	
		= 202.92 mm	
		= 230 mm	
	Eff. Depth,d	= 204 mm	
3	Load Calculations		
	Unit weight of Concrete	= 25 KN/m^3	
	Dead load of Slab	= 5.75 KN/m^2	
	Floor finishes	= 1.5 KN/m^2	
	Partitions	= 0 KN/m^2	
	Extra loads due to filling, surki , etc., if any	= 0 KN/m^2	
	Live Load	= 5 KN/m^2	
	Total Load	= 12.25 KN/m^2	
	Design Load	= 18.375 KN/m^2	
4	Calculation of Bending Moment		
	Edge condition of Slab	= 9 9.Four Edges discontmeous	Edge conditions,As per IS456:2000, D-1.1and 24.4.1
	Ly/Lx, ratio	= 7.1 / 6.9	
		= 1.029	
		= The slab is Two way Slab	

For SREE SHARADHA AMBAL FOUNDATIONS

Partner


For SREE SHARADHA AMBAL FOUNDATIONS

Partner

Dr. ALEX JACOB
B.E., M.Tech(Str), Ph.D(Hon),
M.I.E. (Aust), M.I.E. (Ind)
STRUCTURAL ENINEER
70, BEACH ROAD, KALAKSHETRA COLONY,
Chennai - 600 090.
REG No. SE/GR-I/24/02/001
REG No. RSE100392025

Design of Two way Slab	The values are Displayed in Blue color are the Input values	References

1 Design Datas



S.No	Direction & Sign	Moment Co-efficients	Moment KN.m	
1	X - Negative	0	0	(alpha x * wu *lx^2)
2	X - Positive	0.058	50.74	(alpha x * wu *lx^2)
3	Y- Negative	0	0	(alpha y * wu *lx^2)
4	Y- Positive	0.056	48.99	(alpha y * wu *lx^2)

(B.M co-eff fromm Annex D, clause D.1.1, IS:456:2000)

M,max = 50.74 KN/m

5 Effective depth required

Mu,lim = (0.36 x Fck x (xu,max/d) x (1- 0.42(xu,max/d)) x bd^2

xu,max/d = 0.46

Mu,lim = 3.34 bd^2

d,reqd = (Mu,lim/Qb)$^{1/2}$

= (50740000 / (3.34 x 1000))$^{1/2}$

= 123.25 mm

123.25 < 204

O.K

(IS:456:2000, Annex G, clause G.1.1.c)

6 Reinforcement Calculations

S. N	Dn & Sign	Mu/bd^2	pt from SP16	pt, min	pt,provided	Ast, mm^2
1	x -ve	0	0	0.12	0.12	244.8
2	x +ve	1.22	0.298	0.12	0.298	607.92
3	y -ve	0	0	0.12	0.12	244.8
4	y +ve	1.18	0.287	0.12	0.287	585.48

pt = 100Ast/bd

Ast = (pt/100)xbd

(Minimum reinforcement of slab shall be provide as per IS456:2000, clause 26.5.2.1)

7 Spacing of reinforcement

Spacing, mm		Spacing provided, mm	Ast provided, mm^2
Actual	Maximum		
461.76	300	150	753.6
185.95	300	150	753.6
461.76	300	150	753.6
193.07	300	150	753.6

Spacing = (ast x 1000)/Ast

where,
ast= C/s area of bar
Ast=Area of reinforcement provided

max distance of tension reinforcement bars 3d or 300mm which ever is less As per IS:456:2000, Clause 26.3.3.b

8 Check for deflection

close

close

lx/d, Actual = 33.82

l/d, Max = B.V x M.F

pt, = 100Ast/bd

= 0.3694

fs = 0.58x fyx(Ast required/Ast provided)

fs = 233.94 N/mm^2

Modification Factor = 1.41

l/d, Max = 1.41 X 26

= 36.66

36.66>33.82

O.K

From Fig 4, IS456:2000

For SREE SHARADHA AMBAL FOUNDATIONS


Partner

For SREE SHARADHA AMBAL FOUNDATIONS

Partner

Dr. ALEX JACOB
B.E., M.Tech(Str), Ph.D(Hon),
M.I.E. (Aust), M.I.E. (Ind)
STRUCTURAL ENINEER
70, BEACH ROAD, KALAKSHETRA COLONY,
Chennai - 600 090.
REG No. SE/GR-I/24/02/001
REG No. RSE100392025

	Design of Two way Slab	The values are Displayed in Blue color are the Input values	References
1	Design Datas		



9	Torsional Reinforcement					As per IS456:2000, ANNEX D, clause D-1.8
			lx		ly	
	Size of torsinal reinforcement mesh (lx/5 and ly/5)	=	1380	x	1420 mm	
	Ast required to resist the torsion	=	3/4 times of mid-span Ast			
		=	455.94 mm^2			
	dia of torsional reinforcement	=	8 mm			
	Spacing required	=	110 mm			
	Spacing Provided	=	200 mm			
	No of layers	=	4 Nos (Each 2 top and bottom)			

NOTE:


1. Torsion reinforcement shall be provided at any corner where the slab is simply supprted on both edges meeting at that corner

2. Torsion reinforcement equal to half that described above shall be provided a at corner contained by edges over only one of which the slab is continuous

3. Torsion reinforcements need not be provided at any corner contained by edges over both of which the slab is continuous

9 Reinforcement Details

Direction	Reinforcement
X	Y12 @150mm c/c
Y	Y12 @150mm c/c



For SREE SHARADHA AMBAL FOUNDATIONS

Partner

For SREE SHARADHA AMBAL FOUNDATIONS

Partner

Dr. ALEX JACOB
B.E., M.Tech(Str), Ph.D(Hon),
M.I.E. (Aust), M.I.E. (Ind)
STRUCTURAL ENINEER
70, BEACH ROAD, KALAKSHETRA COLONY,
Chennai - 600 090.
REG No. SE/GR-I/24/02/001
REG No. RSE100392025

THE LANDLENS SUITE

Eight ways to know a piece of land before you pay for it.

This report covers one part of the picture. These cover the rest, drawn from the same government records, for any property in Tamil Nadu.

LandLens One
Ask anything about a property and get an answer grounded in live government records, with the sources shown.
/landlens/one

Verify My Land
Every record check run on one property and returned as a single report.
/landlens/verify-my-land

Legal Opinion
An advocate's written opinion on the title, built on the records we pull for it.
/landlens

One Map
Every layer on one map: the parcel, its boundary, zoning, water bodies and what sits around it.
/landlens/one/map

PriceMap
What land actually changed hands for around this plot, taken from the registered deeds.
/landlens/pricemap

Build Scope
What you are allowed to build here: floor space, height, coverage and setbacks.
/landlens/build-scope

Property Tracker
Watch a property and hear about it when something new is registered against it.
/landlens/property-tracker

Deal Room
Run the transaction in one place: documents, stamping, signatures and the parties.
/landlens/deal-room

FREE TOOLS · NO ACCOUNT NEEDED

Twenty-four checks you can run yourself, at no cost.

Records and verification

The registers themselves, read for you.

- Encumbrance Certificate
- Patta and Chitta
- Field Measurement Sketch
- EC Analyzer
- Bank charge check
- Court case search
- Seller background check
- Approval check by survey

Value and duty

What it is worth and what it costs to register.

- Guideline value by street
- Guideline value by survey
- Stamp duty and registration fees
- Capital gains
- Floor space index
- Area unit converter

Zoning and land use

What the plan says can happen on this land.

- Land use zone finder
- CMDA land use check
- Coastal regulation zone
- Master plan check
- Water bodies finder
- Airport height clearance

Registers and directories

Who holds it, and which office keeps the record.

- Find your registering office
- Temple property check
- Waqf property check
- RERA register

Every free tool
/tools

Services we run for you
/services

The LandLens suite
/landlens/one

Verified RealEstate™

Every claim in this document traces back to a government record.

- Legal opinions, due diligence and title verification
- Building plan, layout and sub-division approvals
- Completion and occupancy certificates, regularisation
- Escrow, negotiation and NRI property management
- Land survey, soil testing, architecture and construction

Verified RealEstate
3/350/2 Mettukuppam,
OMR Thoraipakkam,
Chennai 600 097, India
hello@verified.realestate
+91 9996 12 9996

Prepared from the registers named on the page each finding sits on. Where a register could not be read, this document says so in its place rather than leaving the gap to be read as a clean result.