Verified RealEstate™

Your trusted partner for buying, selling, and managing property, ensuring hassle-free service with 100% transparency.

3/350/2 Mettukuppam,
OMR Thoraipakkam,
Chennai, India

hello@verified.realestate
+91 9996 12 9996

Official Property Record

Digitally Verified Record - Powered by Verified RealEstate™



No. 50, Kirupasankari Street, West Mambalam, Chennai - 600 033. Ph: 044-2485 4603.
E-Mail : boumace@gmail.com

BOURN&
CONSULTANTS- ENGINEERS

S.P.S. Inbarajan, M E (Structural)
Structural Consultant

Date: 14.03.2025

STRUCTURAL DESIGN STABILITY CERTIFICATE.

It is certified that the Proposed Residential Building of Stilt+ Four Floors Residential Building with 16 Dwelling units at Door No: 326/1 to 326/6& 328/1 to 328/6, Block No: 174& 175, Kurinji Colony, 4th Avenue and 6th Street, Shanthi Colony, Anna Nagar, Chennai Comprised in T.S.No:60/1, Block No: 19 of Koyambedu Village within the limits of Greater Chennai Corporation. Has been done by me/us based on the report of Geotechnical investigation (Soil test) done by Report No: 006/BRP/24-25 Dated: 30.05.2024 and considering the functional requirement of the building. I/We have been designed as a RCC structure to withstand the Dead Load, Imposed Load and Wind Load / Earthquake loads ensuring Structural Safety and service ability as per the norms and guidelines prescribed in the following codes of Bureau of Indian Standards.

2. It is certified that among other factors, the Proposed Building has been designed to resist Earthquake. I/We have checked various parameters and found that the proposed building would be Safe.

3. I/We further certify that:

I. IS: 456-2000 Code of Practice for Plain and Reinforced concrete.
2. IS: 875-1987 Code of Practice for Design loads for Buildings and Structures.
3. IS: 1893-2002 Criteria for Earthquake resistant design of Structures Part-I general Provisions and Buildings.
4. IS: 4236-1993 Code of Practice for Earthquake resistant design & Construction of Buildings.
5. IS: 13920-1993 Code of Practice for Ductile detailing of concrete structures subjected to seismic forces and
6. National Building code of India - 2005.

It is further certified that the above structures will be constructed from foundation to roof as per structural designs and detailing of reinforcements furnished in our drawings.

4. Hence, I hereby certify that the Building will be structurally safe and sound for occupation.

For BOURNA CONSULTANTS ENGINEERS,

(S.P.S. INBARAJAN.)
Chief Consultant.

S. P. S. INBARAJAN
M.E., (Structural) A.M.I.E.,
Structural Consultant
Registered Structural Engineer
Grade-I (RSE) in Greater Chennai Corporation
Reg/ No. RSE 100302019 dt. 30.09.2019
Door No.50, Kirupasankari Street,
West Mambalam, Chennai-600 033.

DESIGN BASIS REPORT

FOR

M/S.INDIA BUILDERS

THE PROPOSED CONSTRUCTION OF RESIDENTIAL BUILDING WITH 16 DWELLING UNITS AVAILING PREMIUM FSI WITH TOD BENEFIT AT DOOR NO:326/1 TO 326/6 TO 3286, BLOCK NO:174& 175, KURINJI COLONY, 4TH AVENUE AND 6TH STREET SHANTHI COLONY, ANNA NAGAR, CHENNAI, COMPRISED IN T.S.NO:60/1, BLOCK NO:19 OF KOYAMBEDU VILLAGE WITHIN THE LIMITS OF GREATER CHENNAI CORPORATION.ZONE: 8,DIVISION: 99.

S. P S. INBARAJAN, M.E (Struct)
Registered Structural Engineer
Grade-I (SE) in CMDA
Reg. No. SE/GR-1/2024/02/009 dt. 27.02.2024
Grade-I (RSE) in Greater Chennai Corporation
Reg. No. RSE 100302019 Dt. 30.09.2019
Door No.50, Kirupasankari Street,
West Mambalam, Chennai-600 033.

TABLE OF CONTENTS

1.0 OBJECTIVE

2.0 DESIGN LOADS

2.1 Dead Loads

2.2 Imposed Loads

2.3 Earthquake Loads

2.4 Load Combinations

3.0 ANALYSIS METHOD

4.0 DESIGN ASSUMPTION

5.0 FOUNDATION DESIGN

6.0 MATERIALS

7.0 NOMINAL COVER TO REINFORCEMENT

S. P S. INBARAJAN, M.E.. (Struct)
Registered Structural Engineer
Grade-I (SE) in CMDA
Reg. No. SE/GR-1/2024/02/009 dt. 27.02.2024
Grade-I (RSE) in Greater Chennai Corporation
Reg. No. RSE 100302019 Dt. 30.09.2019
Door No.50, Kirupasankari Street,
West Mambalam, Chennai-600 033.

1.0 OBJECTIVE

The Design basis covers the basic requirement that will be followed for the design of THE PROPOSED CONSTRUCTION OF RESIDENTIAL BUILDING WITH 16 DWELLING UNITS AVAILING PREMIUM FSI WITH TOD BENEFIT FOR M/S.INDIA BUILDERS AT DOOR NO:326/1 TO 326/6 TO 3286, BLOCK NO:174& 175, KURINJI COLONY, 4TH AVENUE AND 6TH STREET SHANTHI COLONY, ANNA NAGAR, CHENNAI, COMPRISED IN T.S.NO:60/1, BLOCK NO:19 OF KOYAMBEDU VILLAGE WITHIN THE LIMITS OF GREATER CHENNAI CORPORATION.ZONE: 8,DIVISION: 99.

The building is designed for Stilt + Four Floors. The structure is supported on column in turn resting on Pile Foundation. The Structural system comprises columns, beams, slabs and wall structure.

3-D Analysis of all the building structures will be carried out using STAAD PRO software package and analysis results shall be used for designing the various elements.

2.0 DESIGN LOADS

2.1 Dead Loads

The Dead loads that are envisaged to act permanently are considered as per IS**: 875 (Part 1) – 1987 – Dead loads.** Indian Standard **"Code of Practice for Design Loads (other than earthquake) for Buildings and Structures"**.

1. Slab is assumed to be 150mm thick – 3.75 KN/m²
2. Slab is assumed to be 125mm thick – 3.125 KN/m²
3. Floor finish – 1.5KN/m²
4. Brick work masonry walls 230thick are proposed to be used (location of walls per Architectural drawings) Unit weight is taken as 20 KN/m^3
5. Weathering course in Terrace finish – 3 KN/m^2

S P S. INBARAJAN, M.E. (Struct)
Registered Structural Engineer
Grade-I (SE) in CMDA
Reg. No. SE/GR-1/2024/02/009 dt. 27.02.2024
Grade-I (RSE) in Greater Chennai Corporation
Reg. No. RSE 100302019 Dt. 30.09.2019
Door No.50, Kirupasankari Street,
West Mambalam, Chennai-600 033.

2.2 Imposed Loads

The imposed loads that are envisaged to act permanently are considered as per **IS : 875 (Part 2) – 1987** . Indian Standard **"Code of Practice for Design Loads (other than earthquake) for Buildings and Structures"**.

1. Living = 2 KN/m^2
2. Staircase = 4 KN/m^2
3. Toilets = 2 KN/m^2
4. Terrace floors = 1.5 KN/m^2

2.3 Earthquake Load

The loading due to earthquake is assessed based on the provisions of **IS: 1893-2016**. Structure with ductile detailing is considered as per **IS: 13920-2016.**

CHENNAI falls under Seismic Zone III

Zone factor	=	**0.16**
Response reduction factor	=	**5**
Importance factor	=	**1.0**

Structure with ductile detailing is considered as per IS: 13920-2016

2.4 Load Combinations

The various loads shall be combined in accordance with the stipulations in IS: 875 (Part 5) – 1987. Whichever combinations produced the most unfavorable effect in the building, foundations or structural member concerned shall be adopted. The various load combinations considered in the analysis are as follows:

1. 1(DL+LL)
2. 1 DL+0.8 LL+ 0.8 SQX +1
3. 1 DL+0.8 LL+ 0.8 SQX -1
4. 1 DL+0.8 LL+ 0.8 SQZ +1
5. 1 DL+0.8 LL+ 0.8 SQZ -1

6. 1.0 (DL+SQX +)
7. 1.0 (DL+SQX -1)
8. 1.0 (DL+SQZ +1)
9. 1.0 (DL+SQZ -1)
10. 1.5(DL+LL)
11. 1.5(DL+SQX +1)
12. 1.5(DL+SQX -1)
13. 1.5(DL+SQZ +1)
14. 1.5(DL+SQZ -1)
15. 1.2(DL+LL+SQX +1)
16. 1.2(DL+LL+SQX -1)
17. 1.2(DL+LL+SQZ +1)
18. 1.2(DL+LL+SQZ -1)
19. 0.9DL+1.5SQX+1
20. 0.9DL+1.5SQX -1
21. 0.9DL+1.5SQZ +1
22. 0.9DL+1.5SQZ -1

The above load combinations will be considered and effect of worst combinations Will be taken for design of various building elements.

3.0 ANALYSIS METHODS

The analysis of the structures is carried out using the STAAD PRO. The entire super-structure is modeled using frame elements as appropriate. Beams and columns are modeled as frame elements. Appropriate loads and its combinations, as per relevant IS code clauses, for most unfavorable effects are chosen for design. Various load cases considered in the analysis are briefed above.

4.0DESIGNASSUMPTION

4.1.1 The Base of the Foundation is assumed to be FIXED.

4.1.2 AllConcreteelementsshallbedesignedinaccordancewithIS456:2000LimitState Design.

4.1.3 Appropriate loads and its combinations, as per relevant clauses, for themostunfavorableeffectsarechosenfordesign.(ReferLoadCombinationbelow) .

5.0FOUNDATIONDESIGN

Type of Foundation : Pile foundation.

Depth of Foundation : 25m

6.0MATERIALS

Theself-weightofthevariouselementsarecomputedbasedontheunitweightofmaterialsasgivenb

S.no	Materials	Unit weight KN/m^3
1	Reinforced Cement Concrete	25
2	Solid Block/Brick	20
3	Steel	78.50

Structural concrete shall be of grade M25 for Pile

Structural concrete shall be of grade M20 for Pile cap& Column

Structural concrete shall be of grade M20for Beam & Slab

Steel reinforcement shall be of Grade Fe500 confirming toIS:1786-2008.

7.0NOMINALCOVERTOREINFORCEMENT

From Durability requirement, exposure condition is assumed as mild for structural elements above ground level and mode rate for structural elements below ground level.

The Clear cove to reinforcement to meet durability requirement shall be as follows:

Column –40mm

Pile cap – 100mm

Beam – 25mm

Slab – 20mm

DESIGN OF BEAM: 1

Beam size: 230mm x 450mm

Bending moment at support = 140kNm

Bending moment at mid span = 133kNm

Shear force, Vu = 149kN

Bending moment at support, Mu = 140kNm

$R = (140 \times 10^6)/230x409^2$

$= 3.64$

Pt/100 =Ast/bd = fck/2fy [1-Sq.rt (1-4.598xR/fck)\

fck = 20 N/mm^2

fy = 500 N/mm^2

Pt = 1.07%

Ast required = 1013 mm^2

Provide 6nos of 16Y

Ast provided = 1206 mm^2

Hence safe.

Bending moment at mid span, Mu = 133kNm

$R = (133 \times 10^6)/230 \times 409^2$

$= 3.46$

Pt = 1.0%

Ast required = 944 mm^2

Provide 6nos of 16Y

Ast provided = 1206 mm^2

Hence it is safe

Shear force, Vu, = 149kN

τv = Vu/bd

= $(149 \times 10^3)/ 230 \times 409$

= $1.58\ N/mm^2$

Hence ok.

Shear capacity of concrete:

Pt = 1.0 %

τc = 0.62

= τc bd

= 0.62X 230 X 409

= 58323 N (or) 58 kN

Shear to be carried by stirrups

Vu = Vs – τc bd

= 149 – 58 kN

= 91kN

Therefore, provide 2 legged 10Y @ 150 mm C/C at the supports.

Provide 2 legged 10Y @ 200mm C/C at the midspan.

DESIGN OF BEAM: 2

Beam size: 230mm x 525mm

Bending moment at support = 132kNm

Bending moment at mid span = 111kNm

Shear force, Vu = 96kN

Bending moment at support, Mu = 132kNm

R = $(132 \times 10^6)/230x484^2$

= 2.44

Pt/100 =Ast/bd = fck/2fy [1-Sq.rt (1-4.598xR/fck)\

fck = 20 N/mm^2

fy = 500 N/mm^2

Pt = 0.65%

Ast required = 725 mm^2

Provide 4nos of 16Y

Ast provided = 804 mm^2

Hence safe.

Bending moment at mid span, Mu = 111kNm

R = (111 x 10^6)/230 x 484^2

= 2.06

Pt = 0.53%

Ast required = 593 mm^2

Provide 4 nos of 16Y

Ast provided = 804 mm^2

Hence it is safe

Shear force, Vu, = 96kN

τ_v = Vu/bd

= 96 x 10^3 / 230 x 484

= 0.86 N/mm^2

Hence ok.

<u>Shear capacity of concrete:</u>

Pt = 0.65 %

τ_c = 0.53

= τ_c bd

= 0.53 X 230 X 484

	=	58999 N (or) 59kN

Shear to be carried by stirrups

Vu	=	Vs – $\bar{C}$c bd
	=	96 – 59 kN
	=	37kN

Therefore, provide 2 legged 8Y @ 100 mm C/C at the supports.

Provide 2 legged 8Y @ 200 mm C/C at the midspan.

Design of Pile Cap :

Safe load for 600mm Dia pile	=	1130 KN
Concrete grade for pile cap	=	M20
Un factored Column load	=	1442KN
No of piles required	=	1442/1130 = 1.28
Provide 2 nos of Pile (600Ø)		
Spacing of Piles	=	1800mm
	=	1.8m
Factored load	=	1442 x 1.5
	=	2163
Bending moment WL/4	=	2163 x 1.8 / 4
	=	973KNM
R = MU/bd^2	=	973 x 10^6 / 975 x 875^2
	=	1.3
fck	=	20N/mm^2
fy	=	500N/mm^2
Pt/100 = Ast/bd	=	fck/2fy [1-sqrt (1 - 4.598xR/20)]

Ast required = 2739 mm^2

Provide 7 nos of 25 Dia bar

Ast provided = 3437mm^2

Ast required > Ast provided

Hence it is safe.

DESIGN OF COLUMN C1

Length of column	D	450	mm
Breadth of column	b	230	mm
Unsupported length (longer direction)	L_x	2700	mm
Unsupported length (shorter direction)	L_y	2700	mm
Eff. Length (longer direction)	L_{ex}	2160	mm
Eff. Length (shorter direction)	L_{ey}	2160	mm
Factored Load	P_u	1051	kN
Factored moment (longer direction)	Mux	65	kNm
Factored moment (shorter direction)	Muz	21	kNm
Charac. comp strength of concrete	f_{ck}	20	N/mm^2
Yield stress of steel	f_y	500	N/mm^2
Dia of bar used	Φ	20	mm
Clear cover		40	mm
Effective cover	d'	50	mm
Effective depth	d	400	mm
Check for slenderness			
Longer Direction			
Slenderness ratio	L_{ex}/D	4.80	**short**
Additional moment due to slenderness	M_{ax}	0	kN-m
Shorter Direction			
Slenderness ratio	L_{ey}/b	9.39	**short**
Additional moment due to slenderness	M_{ay}	0	kN-m
Calculation of P_{uz}			
No of bars used		8	
Area of reinforcement	Ast	2512	
Provided steel		8 nos Y20	
Percentage of reinforcement	p_t	2.427	%
Area of concrete	Ag	103500	mm^2
Ultimate axial load (without moments)	P_{uz}	1851	kN
Calculation of P_b:			
Longer Direction			
	d'/D	0.111	
Coefficient k_1(from TABLE 60 of SP:1980)	k_{1x}	0.204	From Sp16
Coefficient k_2(from TABLE 60 of SP:1980)	k_{2x}	0.398	
Axial load corresponding to balanced failure	P_{bx}	523	kN
Reduction factor for additional moments	k_x	1.000	
Moment due to slenderness	M_{ax}	**0.00**	kN-m
Shorter Direction			
	d'/b	0.217	
Coefficient k_1(from TABLE 60 of SP:1980)	k_{1y}	0.179	
Coefficient k_2(from TABLE 60 of SP:1980)	k_{2y}	0.143	
Axial load corresponding to balanced failure	P_{by}	406	kN
Reduction factor for additional moments	k_y	0.554	
Moment due to slenderness	M_{ax}	**0.00**	kN-m
Check for moments due to min. eccentricity			
Longer Direction			
Minimum eccentricity	e_x	20.40	mm

Moment due to min. eccentricity		M_x	21.44	kN-m
Moment in longer direction		M_{ux}	65.00	kNm
Shorter direction				
Minimum eccentricity		e_y	13.07	mm
Moment due to min. eccentricity		M_y	13.73	kN-m
Moment in shorter direction		M_{uy}	21	kNm
Final design moments				
Moment in longer direction		M_{ux}	**65.00**	kNm
Moment in shorter direction		M_{uy}	**21.00**	kNm
Check for interaction				
		d'/D	0.111	
		d'/b	0.217	
p/f_{ck}		p/f_{ck}	0.121	
$P_u/f_{ck}bD$ value		$P_u/f_{ck}bD$	0.508	
$M_{ux1}/f_{ck}bD^2$ value (from SP 16:1980 charts)		$M_{ux1}/f_{ck}bD^2$	0.130	
Uniaxial moment capacity (longer direction)		M_{ux1}	**121.095**	kNm
$M_{uy1}/f_{ck}bD^2$ value (from SP 16:1980 charts)		$M_{uy1}/f_{ck}bD^2$	0.110	
Uniaxial moment capacity (shorter direction)		M_{uy1}	**52.371**	kNm
P_u/P_{uz} ratio		P_u/P_{uz}	**0.568**	
Value of exponent			1.614	
Interaction ratio			**0.595**	
Percentage reinforcement satisfactory or not			**safe**	
b/D ratio		b/D	0.51111111	
Status of dimensions			**OK**	
Gross area		A_g	103500	mm^2
Area of core		A_k	60800	mm^2
Spacing of lateral ties		S	57.5	mm
Larger dimension of the hoop		H	230	mm
Cross sectional area of hoop		A_{sh}	66.87	mm^2

DESIGN OF COLUMN C2

Length of column	D	375	mm
Breadth of column	b	300	mm
Unsupported length (longer direction)	L_x	2700	mm
Unsupported length (shorter direction)	L_y	2700	mm
Eff. Length (longer direction)	L_{ex}	2160	mm
Eff. Length (shorter direction)	L_{ey}	2160	mm
Factored Load	P_u	895	kN
Factored moment (longer direction)	Mux	41	kNm
Factored moment (shorter direction)	Muz	11	kNm
Charac. comp strength of concrete	f_{ck}	20	N/mm^2
Yield stress of steel	f_y	500	N/mm^2
Dia of bar used	Φ	16	mm
Clear cover		40	mm
Effective cover	d'	48	mm
Effective depth	d	327	mm
Check for slenderness			
Longer Direction			
Slenderness ratio	L_{ex}/D	5.76	**short**
Additional moment due to slenderness	M_{ax}	0	kN-m
Shorter Direction			
Slenderness ratio	L_{ey}/b	7.20	**short**
Additional moment due to slenderness	M_{ay}	0	kN-m
Calculation of P_{uz}			
No of bars used		8	
Area of reinforcement	Ast	1607.68	
Provided steel		8 nos Y16	
Percentage of reinforcement	p_t	1.429	%
Area of concrete	Ag	112500	mm^2
Ultimate axial load (without moments)	P_{uz}	1601	kN
Calculation of P_b:			
Longer Direction			
	d'/D	0.128	
Coefficient k_1(from TABLE 60 of SP:1980)	k_{1x}	0.200	From Sp16
Coefficient k_2(from TABLE 60 of SP:1980)	k_{2x}	0.358	
Axial load corresponding to balanced failure	P_{bx}	508	kN
Reduction factor for additional moments	k_x	1.000	
Moment due to slenderness	M_{ax}	**0.00**	kN-m
Shorter Direction			
	d'/b	0.160	
Coefficient k_1(from TABLE 60 of SP:1980)	k_{1y}	0.193	
Coefficient k_2(from TABLE 60 of SP:1980)	k_{2y}	0.281	
Axial load corresponding to balanced failure	P_{by}	479	kN
Reduction factor for additional moments	k_y	0.629	
Moment due to slenderness	M_{ax}	**0.00**	kN-m
Check for moments due to min. eccentricity			
Longer Direction			
Minimum eccentricity	e_x	17.90	mm

Moment due to min. eccentricity		M_x	16.02	kN-m
Moment in longer direction		M_{ux}	41.00	kNm
Shorter direction				
Minimum eccentricity		e_y	15.40	mm
Moment due to min. eccentricity		M_y	13.78	kN-m
Moment in shorter direction		M_{uy}	13.783	kNm
Final design moments				
Moment in longer direction		M_{ux}	**41.00**	kNm
Moment in shorter direction		M_{uy}	**13.78**	kNm
Check for interaction				
		d'/D	0.128	
		d'/b	0.160	
p/f_{ck}		p/f_{ck}	0.071	
$P_u/f_{ck}bD$ value		$P_u/f_{ck}bD$	0.398	
$M_{ux1}/f_{ck}bD^2$ value (from SP 16:1980 charts)		$M_{ux1}/f_{ck}bD^2$	0.090	
Uniaxial moment capacity (longer direction)		M_{ux1}	**75.9375**	kNm
$M_{uy1}/f_{ck}bD^2$ value (from SP 16:1980 charts)		$M_{uy1}/f_{ck}bD^2$	0.090	
Uniaxial moment capacity (shorter direction)		M_{uy1}	**60.75**	kNm
P_u/P_{uz} ratio		P_u/P_{uz}	**0.559**	
Value of exponent			1.599	
Interaction ratio			**0.466**	
Percentage reinforcement satisfactory or not			**safe**	
b/D ratio		b/D	0.8	
Status of dimensions			**OK**	
Gross area		A_g	112500	mm^2
Area of core		A_k	70150	mm^2
Spacing of lateral ties		S	75	mm
Larger dimension of the hoop		H	230	mm
Cross sectional area of hoop		A_{sh}	74.98	mm^2

DESIGN OF SLAB S1

ROOF LEVEL SLAB

Design of two way Slab

Basic Data

Grade of concrete (fck)	=	M 20	
Grade of steel (fy)	=	Fe 500	
Thickness of slab (D)	=	125	mm
Clear cover (cc)	=	15	mm
Effective thickness of slab (deff) = 125 - 15 - 8 /2	=	106	mm
Unit weight of concrete	=	25	KN/m^3
Effective Shorter Span (Lx)	=	3.18	m
Effective Longer Span (Ly)	=	3.467	m
Aspect ratio Ly/Lx	=	1.09	**Two way slab**

Edge Condition : **Two adjacent Edges Discontinous**

Load Data

Dead Load = 0.13 x 25	=	3.125	KN/m^2	
Floor finish	=	1.50	KN/m^2	
Imposed Load	=	2.00	KN/m^2	
Total load	=	6.63	KN/m^2	
Design load (Wu) = 1.5 x 6.625	=	**9.94**	KN/m^2	

Moment and Shear Calculations

Short Span Direction

ax for positive moment	1	→	0.035	
	1.1	→	0.04	
	for 1.09 αx	=	0.040	
Positive moment Mx 0.040 x 9.94 x 3.18 ^2	=	**3.97**	KN-m	
ax for negative moment	1	→	0.047	
	1.1	→	0.053	
	for 1.09 αx	=	0.052	
Negative moment Mx : 0.052 x 9.94 x 3.18 ^2	=	**5.27**	KN-m	

Long Span Direction

For positive moment	αy	=	0.035
Positive moment My : 0.035 x 9.94 x 3.18 ^2	=	**3.52**	KN-m
For negative moment	αy	=	0.047
Negative moment My : 0.047 x 9.94 x 3.18 ^2	=	**4.72**	KN-m

Shear force V_u = 9.94 x 3.2 x 0.5 = **15.80** KN

Check Effective Depth for Bending

Depth required = $(M_x / (0.133x\ fck \times b))^{1/2}$ = 44.50 mm

Depth provided = 125 - 15 - 8 /2 = 106 mm

Hence O.K

Reinforcement calculations

Short Span Direction @ Support

Mu/bd^2 = 5.27 x 10 ^ 6 / (1000 x 106 x 106) = **0.469**

Pt = **0.11** %

Area of steel Ast = 0.00111 x 1000 x 106 = 117.55 mm^2

Minimum area of steel 0.0012 x 1000 x 125 = 150.00 mm^2

Spacing of Y **8** bars 50.27 x 1000 / 150.00 = 334.93 mm

Ast provided = 335.1 mm^2

Check for Spacing

Minimum of

1) 3d = 318 mm

2) = 300 mm

3) = 334.93 mm

Therefore provide Y **8** @ **150** mm C/C

Short Span Direction @ Mid Span

Mu/bd^2 = 3.97 x 10 ^ 6 / (1000 x 106 x 106) = 0.353

Pt = 0.083 %

Area of steel Ast = 0.00083 x 1000 x 106 = 87.982 mm^2

Minimum area of steel 0.0012 x 1000 x 125 = 150.00 mm^2

Spacing of Y **8** bars 50.27 x 1000 / 150.00 = 334.93 mm

Ast provided = 335.1 mm^2

Check for Spacing

Minimum of

1) 3d = 318 mm

2) = 300 mm

3) = 334.93 mm

Therefore provide Y **8** @ **150** mm C/C

Provided % of Tension Reinforcement (pt) = **0.316** %

100

Long Span Direction @ Support

$Mu/bd^2 = \frac{4.72 \times 10 \wedge 6}{1000 \times 106 \times 106} = 0.420$

Pt = 0.099 %

Area of steel Ast = 0.00099 x 1000 x 106 = 105.09 mm^2

Minimum area of steel 0.0012 x 1000 x 125 = 150.00 mm^2

Spacing of Y **8** bars 50.27 x 1000 / 150.00 = 334.93 mm

Ast provided = 335.1 mm^2

Check for Spacing

Minimum of

1) 3d = 318 mm

2) = 300 mm

3) = 334.93 mm

Therefore provide Y **8** @ **150** mm C/C

Long Span Direction @ mid Span

$Mu/bd^2 = \frac{3.52 \times 10 \wedge 6}{1000 \times 106 \times 106} = 0.313$

Pt = 0.073 %

Area of steel Ast = 0.00073 x 1000 x 106 = 77.742 mm^2

Minimum area of steel 0.0012 x 1000 x 125 = 150.00 mm^2

Spacing of Y **8** bars 50.27 x 1000 / 150.00 = 334.93 mm

Ast provided = 335.1 mm^2

Check for Spacing

Minimum of

1) 3d = 318 mm

2) = 300 mm

3) = 334.93 mm

Therefore provide Y **8** @ **150** mm C/C

Check for Deflection:

Basic Span/depth Ratio = 22

% of Tension Reinforcement provided (pt) = 0.316 %

Service stress of steel (fs) : 0.58fy(Ast_r/Ast_p) = 76.14 N/mm^2

Modification Factor for Tension Reinforcement (F1) = 2.00

Allowable Span/Eff Depth Ratio = 44

Actual Span/Eff Depth Ratio = 3.18 x 1000 / 106 = 30.00

Hence O.K

DESIGN OF SLAB S2

ROOF LEVEL SLAB

Design of two way Slab

Basic Data

Grade of concrete (fck)	=	M 20	
Grade of steel (fy)	=	Fe 500	
Thickness of slab (D)	=	125	mm
Clear cover (cc)	=	15	mm
Effective thickness of slab (deff) = 125 - 15 - 8 /2	=	106	mm
Unit weight of concrete	=	25	KN/m^3
Effective Shorter Span (Lx)	=	3.35	m
Effective Longer Span (Ly)	=	3.467	m
Aspect ratio Ly/Lx	=	1.03	**Two way slab**

Edge Condition : **Two adjacent Edges Discontinous**

Load Data

Dead Load	= 0.13 x 25	=	3.125	KN/m^2
Floor finish		=	1.50	KN/m^2
Imposed Load		=	2.00	KN/m^2
Total load		=	6.63	KN/m^2
Design load (Wu) = 1.5 x 6.625		=	**9.94**	KN/m^2

Moment and Shear Calculations

Short Span Direction

ax for positive moment	1	→	0.035	
	1.1	→	0.04	
	for 1.03 αx	=	0.037	
Positive moment Mx	0.037 x 9.94 x 3.35 ^2	=	**4.10**	KN-m
ax for negative moment	1	→	0.047	
	1.1	→	0.053	
	for 1.03 αx	=	0.049	
Negative moment Mx :	0.049 x 9.94 x 3.35 ^2	=	**5.48**	KN-m

Long Span Direction

For positive moment	αy	=	0.035	
Positive moment My :	0.035 x 9.94 x 3.35 ^2	=	**3.90**	KN-m
For negative moment	αy	=	0.047	
Negative moment My :	0.047 x 9.94 x 3.35 ^2	=	**5.24**	KN-m

S. P S. INBARAJAN, M.E., (Struct)
Registered Structural Engineer
Grade-I (SE) in CMDA
Reg. No. SE/GR-1/2024/02/009 dt. 27.02.2024
Grade-I (RSE) in Greater Chennai Corporation
Reg. No. RSE 100302019 Dt. 30.09.2019
Door No.50, Kirupasankari Street,
West Mambalam, Chennai-600 033.

Shear force V_u = 9.94 x 3.4 x 0.5 = **16.65** KN

Check Effective Depth for Bending

Depth required = $(M_x / (0.133x\ fck \times b))^{1/2}$ = 45.37 mm

Depth provided = 125 - 15 - 8 /2 = 106 mm

Hence O.K

Reinforcement calculations

Short Span Direction @ Support

Mu/bd^2 = $\frac{5.48 \times 10 \wedge 6}{1000 \times 106 \times 106}$ = **0.487**

Pt = **0.12** %

Area of steel Ast = 0.00115 x 1000 x 106 = 122.33 mm^2

Minimum area of steel 0.0012 x 1000 x 125 = 150.00 mm^2

Spacing of Y **8** bars 50.27 x 1000 / 150.00 = 334.93 mm

Ast provided = 402.12 mm^2

Check for Spacing

Minimum of

1) 3d = 318 mm

2) = 300 mm

3) = 334.93 mm

Therefore provide Y **8** @ **125** mm C/C

Short Span Direction @ Mid Span

Mu/bd^2 = $\frac{4.10 \times 10 \wedge 6}{1000 \times 106 \times 106}$ = 0.365

Pt = 0.086 %

Area of steel Ast = 0.00086 x 1000 x 106 = 90.868 mm^2

Minimum area of steel 0.0012 x 1000 x 125 = 150.00 mm^2

Spacing of Y **8** bars 50.27 x 1000 / 150.00 = 334.93 mm

Ast provided = 402.12 mm^2

Check for Spacing

Minimum of

1) 3d = 318 mm

2) = 300 mm

3) = 334.93 mm

Therefore provide Y **8** @ **125** mm C/C

Provided % of Tension Reinforcement (pt) = **0.379** %

100

Long Span Direction @ Support

S. P S. INBARAJAN, M.E., (Struct)
Registered Structural Engineer
Grade-I (SE) in CMDA
Reg. No. SE/GR-1/2024/02/009 dt. 27.02.2024
Grade-I (RSE) in Greater Chennai Corporation
Reg. No. RSE 100302019 Dt. 30.09.2019
Door No.50, Kirupasankari Street,
West Mambalam, Chennai-600 033.

$Mu/bd^2 = \frac{5.24 \times 10 \wedge 6}{1000 \times 106 \times 106} = 0.467$

Pt = 0.110 %

Area of steel Ast = 0.00110 x 1000 x 106 = 116.96 mm^2

Minimum area of steel 0.0012 x 1000 x 125 = 150.00 mm^2

Spacing of Y **8** bars 50.27 x 1000 / 150.00 = 334.93 mm

Ast provided = 335.1 mm^2

Check for Spacing

Minimum of

1) 3d = 318 mm

2) = 300 mm

3) = 334.93 mm

Therefore provide Y **8** @ **150** mm C/C

Long Span Direction @ mid Span

$Mu/bd^2 = \frac{3.90 \times 10 \wedge 6}{1000 \times 106 \times 106} = 0.347$

Pt = 0.082 %

Area of steel Ast = 0.00082 x 1000 x 106 = 86.458 mm^2

Minimum area of steel 0.0012 x 1000 x 125 = 150.00 mm^2

Spacing of Y **8** bars 50.27 x 1000 / 150.00 = 334.93 mm

Ast provided = 335.1 mm^2

Check for Spacing

Minimum of

1) 3d = 318 mm

2) = 300 mm

3) = 334.93 mm

Therefore provide Y **8** @ **150** mm C/C

Check for Deflection:

Basic Span/depth Ratio = 22

% of Tension Reinforcement provided (pt) = 0.379 %

Service stress of steel (fs) : 0.58fy(Ast_r/Ast_p) = 65.53 N/mm^2


Modification Factor for Tension Reinforcement (F1) = 2.00

Allowable Span/Eff Depth Ratio = 44

Actual Span/Eff Depth Ratio = 3.35 x 1000 / 106 = 31.60

Hence O.K

S P S. INBARAJAN, M.E (Struct)
Registered Structural Engineer
Grade-I (SE) in CMDA
Reg. No. SE/GR-1/2024/02/009 dt. 27.02.2024
Grade-I (RSE) in Greater Chennai Corporation
Reg. No. RSE 100302019 Dt. 30.09.2019
Door No.50, Kirupasankari Street,
West Mambalam Chennai-600 033.



S. P. S. INBARAJAN, M.E., (Struct)
Registered Structural Engineer
Grade-I (SE) in CMDA
Reg. No. SE/GR-1/2024/02/009 dt. 27.02.2024
Grade-I (RSE) in Greater Chennai Corporation
Reg. No. RSE 100302024 Dt. 09.10.2024
Door No.50, Kirupasankari Street,
West Mambalam, Chennai-600 033.



our services doesn't just end there

Buying & Selling Services

Property Buying Assistance, Property Selling Support, Market Price Analysis, Owner Outreach and Negotiation.

Legal & Documentation Services

Certified EC, Patta, legal opinions, property verification, due diligence, litigation solutions, and legal heir certificates.

Property Development & Approvals

Building plan approvals, construction, layout and sub-division approvals, zone conversion, and occupancy certification.

NRI & Investment Services

Escrow Services, Rentals, Litigation Solutions, Property Valuation and Property Management

Compliance & Special Services

Demolition, Vaasthu checks, regularization of unauthorized buildings, and office space solutions.



empowering your real estate decisions with smart tools

Property Valuation & Cost Estimation

Guideline Value, Apartment Composite Value, Stamp Duty & Registration Fees Calculator, Building Value Calculator, Capital Gains Calculator, Area Unit Converter, Length Unit Converter

Ownership, Compliance & Legal Verification

Encumbrance Certificate (EC) Search, Find Your SRO, Temple Property Check, WAQF Property Check, View Patta/Chitta, View FMB, Patta Analyzer, EC Analyzer

Zoning & Land Use Analysis

Land Use Zone Finder, CRZ Zone Check, Aquifer Zone Check, CBA Check, EWS Check, Road Width Check, Proposed Road Widening Check, FSI Calculator

Property Documentation & Workflow Tools

Forms & Templates, Document Generator, Document Translation, Dictionary

Vastu & Property Management Tools

Home Vastu Shastra, Plot Vastu Shastra, Property Management

Verified RealEstate™

We're honored to be part of your real estate journey

3/350/2 Mettukuppam,
OMR Thoraipakkam,
Chennai, India

hello@verified.realestate
+91 9996 12 9996
www.verified.realestate